


21700129	<b>DATA SHEET</b>	
Valid from: 17.06.2020	<b>ETHERLINE ACCESS U08GT</b>	

## Description

- Fast Ethernet Network-Switch (10/100/1000BaseT(X)), unmanaged
- Ports: 8x RJ45
- Suitable for harsh industrial environment (Protection class IP30)



## General characteristics

### Interfaces & buttons

**RJ45 Port:** 10/100/1000BaseT(X) auto-negotiation, full-/halfduplex-mode and Auto-MDI/MDI-X-connection

### DIP-switch

Activate/deactivate Broadcast Storm Protection

Activate/deactivate Jumbo Frames

### Switch properties

MAC- tablesize: 8 K

packet-bufferize: 4 Mbit

packet forwarding rate: 11.90 Mpps

Jumbo Frame Size: 9.6 KB (max.)

### Temperature range

operating temp.: -10°C to +60°C (14°F to 140°F)

storage temp.: -40°C to +85°C (-40°F to 185°F)

### Relative humidity

5% to 95 % (non-condensing)

### Standards

IEEE 802.3i (10BaseT)

IEEE 802.3u (100BaseTX)

IEEE 802.3ab (1000Base-T)

### Processing type

Store and Forward

### MTBF (mean time between failures)

2.486.867 Std @ Telcordia (Bellcore), GB

## Power requirements

### Connection

1 removable 4- pole terminal block

### Input voltage

24 V AC /V DC (18-30V AC, 50/60Hz; 12-48V DC)

### Power Consumption (max.)

10 W

### Input current (max.)

0.85 A

### Overload current protection

support

### Reverse polarity protection

support

### Redundancy protection

support

## Physical properties

### Housing

metal

### IP class

IP30


### Weight

0.5 kg

### Installation


DIN-rail mounting

Creator: FELI1/PDP	Document: DB21700129EN	Page 1 of 2
Released: IVSE1/PDP	Version: 00	

21700129	<b>DATA SHEET</b>	
Valid from: 17.06.2020	<b>ETHERLINE ACCESS U08GT</b>	

## Technical drawing

Dimensional drawing



## Standards and approvals

Safety	UL61010
EMC	EN55022/CISPR22 Class A
EMI	FCC CFR47 Part 15
EMS	IEC 61000-4-2 ESD: contact: 6kV / air: 8kV IEC 61000-4-3 RS: 80MHz to 2GHz: 10V/m IEC 61000-4-4 EFT/Burst: Power: 2kV / Signal: 1kV IEC 61000-4-5 Surge: Power: 1kV / Signal: 1kV IEC 61000-4-6 CS: 10V (150 kHz – 80 MHz)
Vibration	according IEC 60068-2-6
Shock	according IEC 60068-2-27
Free fall	according IEC 60068-2-31
Approvals	CE UL (E331560) FCC

## Application range

Automation, industrial machinery and plant engineering

## Note

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: FELI1/PDP Released: IVSE1/PDP	Document: DB21700129EN Version: 00	Page 2 of 2
---	---------------------------------------	-------------