


44423180	DATA SHEET	
Valid from: 29.04.2022	EPIC® POWER M12 L / K CONTACTS	

Description

- Male and female contacts for EPIC POWER M12L and M12K connectors



Female contacts for M12L / M12K

Article-nr	Article Description	For cross-section	Variant	Amount of contacts per PU
44423180	EPIC POWER M12 BCM 1.5 AU 0.75-1.5 (10)	0.75-1.5 mm ²	Crimp	10
44423182	EPIC POWER M12 BCM 1.5 AU 2.5 (10)	2.5 mm ²	Crimp	10
44423186	EPIC POWER M12 BCM 1.5 AU 0.75-1.5 (100)	0.75-1.5 mm ²	Crimp	100
44423188	EPIC POWER M12 BCM 1.5 AU 2.5 (100)	2.5 mm ²	Crimp	100
44423414	EPIC POWER M12 BLM 1.5 AU (100)	max. 1.5 mm ²	Solder	100



Male contacts for M12L / M12K

Article-nr	Article Description	For cross-section	Variant	Amount of contacts per PU
44423183	EPIC POWER M12 SCM 1.5 AU 0.75-1.5 (10)	0.75-1.5 mm ²	Crimp	10
44423185	EPIC POWER M12 SCM 1.5 AU 2.5 (10)	2.5 mm ²	Crimp	10
44423189	EPIC POWER M12 SCM 1.5 AU 0.75 (100)	0.75-1.5 mm ²	Crimp	100
44423191	EPIC POWER M12 SCM 1.5 AU 2.5 (100)	2.5 mm ²	Crimp	100
44423412	EPIC POWER M12 SLM 1.5 AU (100)	max. 1.5 mm ²	Solder	100



Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: FELI1/PDP Released: IVSE1/PDP	Document: DB44423180EN Version: 00	Page 1 of 1
---	---------------------------------------	-------------