


70250213	<b>DATA SHEET</b>	
Valid from: 01.12.2021	<b>EPIC® ULTRA H-B 10 AG-QB</b>	

## Description

- Housing H-B ULTRA: For more reliability
- Optimum, low resistance 360° screening
- All-purpose due to high corrosion resistance and high environmental protection
- Space-saving due to compact dimensions
- Faster than any other comparable system
- High mechanical resistance



## General Characteristics

Series	ULTRA H-B 10
Version	Panel mount base
Locking	Double lever
Protection (DIN EN 60529)	IP 68 (latched)
Protection (NEMA 250, UL50E)	4, 4X, 12 (latched)
Temperature Range	-40°C to +100°C


## Materials and Surfaces

Housing	Zinc die-casting, nickel-plated
Lever / Bolt	Stainless steel
Sealing	NBR, conductive



## Standard

Safety Standard	IEC 61984
Product Features after	DIN EN 6988, DIN EN ISO 9227, DIN EN 60068-2-52

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB70250213EN Version: 02	Page 1 of 3
---	---------------------------------------	-------------

70250213	<b>DATA SHEET</b>	
Valid from: 01.12.2021	<b>EPIC® ULTRA H-B 10 AG-QB</b>	

### Technical Drawings



Good chemical resistance



Corrosion resistant



Installation time



Required space



Robust




Connectors with standart housing



Waterproof

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB70250213EN Version: 02	Page 2 of 3
---	---------------------------------------	-------------

70250213	<b>DATA SHEET</b>	
Valid from: 01.12.2021	<b>EPIC® ULTRA H-B 10 AG-QB</b>	

### Info

EMC protection, corrosion-resistant

### Application range

In EMC-sensitive environments

For fixed and flexible applications (e.g. machinery building, wind tribunes)

Construction machinery

Electric motor manufacturing

### Product features

Housing pluggable with standart housing

Corrosion resistant according to DIN EN 6988

Resistance to cyclic salt spray is tested according to DIN EN 60068-2-52, severity level 2

Salt spray testing according to DIN EN ISO 9227, method NSS, period of test 480 hours

### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB70250213EN Version: 02	Page 3 of 3
---	---------------------------------------	-------------