

29033102	DATA SHEET
Valid from: 09.11.2020	GOF DUPLEX Patchcord LC/LC G62,5, 2m

Description

- GOF Optical fiber Patchcord
- Straight LC-Duplex-plug on straight LC-Duplex-plug



General characteristics

Connection method, connector	LC-Duplex (LC-D), beige LC-Duplex (LC-D), beige
Polishing	PC (physical contact)
Number of lead	2
Temperature range	-25°C to +70°C (-13°F to 158°F) (Operation) -25°C to +70°C (-13°F to 158°F) (Storage) -10°C to +60°C (14°F to 140°F) (Installation)

Variation

Article	Description	Fiber type	Jacket colour
29033102	GOF DUPLEX Patchcord LC/LC G62,5, 2m	Multimode OM1 62.5 µm	Orange
29033202	GOF DUPLEX Patchcord LC/LC G50 OM2, 2m	Multimode OM2 50 µm	Orange
29033302	GOF DUPLEX Patchcord LC/LC G50 OM3, 2m	Multimode OM3 50 µm	Turquoise
29033402	GOF DUPLEX Patchcord LC/LC G50 OM4, 2m	Multimode OM4 50 µm	Violet

Additional note

Standard length 2m. Data sheet also valid for variant lengths.

Optical properties

Insertion loss (max.)	0.25 dB / 0.5 dB (mean/ 97%)
Return loss (min.)	45 dB

Mechanical properties

LC-D-Plug


Housing, material	PEI
Ferrule, material	Zirconia
Ferrule-Ø	1.25 mm
Boot, material	TPE, black and red
Tensile strength	100 N
Mating cycles (min.)	1000

Line

Outer coating, material	LSOH
Cable outer diameter	2 mm
Min bending radius	50 mm (Installation) 25 mm (Operation)

29033102	DATA SHEET
Valid from: 09.11.2020	GOF DUPLEX Patchcord LC/LC G62,5, 2m

Technical drawing



Standards / Approvals

Fibre optic connector interfaces – Type LC IEC 61754-20
 Optical fibres – part 2-10: category A1 multimode fibres IEC 60793-2-10

Application range

Office, Data centers, Industry

Note

Photographs are not true to scale and do not represent detailed images of the respective products.