29110988	DATA SHEET
Valid from: 24.05.2018	GOF Connector SC Singlemode APC GR /50PC

Description

- GOF Optical fiber Connector SC-Simplex
- Suitable for singlemode optical fibers
- Push-Pull locking mechanism
- Ideal for assembling

General characteristics

Connector, Type SC-Simplex (SC-S)
Locking mechanism Push-Pull
Suitable optical fibers Singlemode (SM)
Suitable core-Ø (max.) 2.8 mm

Temperature range $-40 \, ^{\circ}\text{C to } +80 \, ^{\circ}\text{C } (-40 \, ^{\circ}\text{F to } +176 \, ^{\circ}\text{F}) \, \text{(Operation)}$ $-40 \, ^{\circ}\text{C to } +85 \, ^{\circ}\text{C } (-40 \, ^{\circ}\text{F to } +185 \, ^{\circ}\text{F}) \, \text{(Storage)}$

Variation

Article	Description	Connector- colour	Polishing	Packing unit [PCS]
29110988	GOF Connector SC Singlemode APC GR /50PC	Green	APC	50
29110989	GOF Connector SC Singlemode APC GR /4PC	Green	APC	4
29110999	GOF Connector SC Singlemode BL /4PC	Blue	PC	4
29110998	GOF Connector SC Singlemode BL /50PC	Blue	PC	50

Additional note

APC = angled physical contact


PC = physical contact

Mechanical properties

Flame retardant acc. to UL 94 V-0
Housing, material PBT
Ferrule, material Zirconia
Ferrule-Ø 2.5 mm
Tensile strength after assembly 100 N

Technical drawing

Dimensional drawing





Standards / Approvals

Fibre optic connector interfaces - Part 4: Type SC

IEC 61754-4

Application range

Office, Data centers, Industry

Note

Photographs are not true to scale and do not represent detailed images of the respective products.

Document: DB29110988EN	Dage 1 of 1
Version: 00	Page 1 of 1