

ÖLFLEX® VFD 1XL

UDB701700EN

Date: March 15, 2020

1. APPLICATION

ÖLFLEX® VFD 1XL is a reduced diameter shielded motor cable with basic continuous flexing features for VFD drives. This robust cable provides exceptional oil and crush resistance required for industrial tray applications. The enhanced electrical properties of XLPE plus insulation provide problem-free performance where precision control is critical. The UL TC-ER allows for installation without conduit, providing material and labor cost savings.

Applications:

VFD drive and motor applications, web presses, HVAC, conveyors, any on/off, slow down/speed up applications utilizing VFD drives and motors.

Underwriters Laboratories

For Tray use in Exposed Run applications as per Article 336 of the National Electrical Code or as Power and Control Cable in Servomotors and VFD drives.

Canadian Standards

Control Instrumentation Cable applications and as Appliance Wiring Material for use in internal or external wiring of electrical and electronic equipment.

2. CABLE DESCRIPTION

- Tinned copper fine wire
- XLPE Plus insulation
- Black color coded conductors with white identification
- Green/Yellow ground wire
- Overall Foil and TC Braid Shield
- Black UV, oil and flame resistant Specially Formulated Thermoplastic Elastomer (TPE)

3. TECHNICAL DATA

Conductor Stranding	16 AWG (1,32 mm ²) to 2 AWG (33,7 mm ²): Class K	
Design / Make-up	Cable is designed in accordance with the requirements of UL Standard 1277 and with CSA standard C22.2 No. 230	
Insulation	Specially formulated Cross Linked Polyethylene (XLPE) Plus	
Color Code	Black conductors with white numbers plus green/yellow (30% stripe width)	
Shield	Tri-laminated Foil and Tinned Copper Braid Shield (85% coverage) Tinned Copper Drain wire	
Outer Sheath	Specially Formulated Thermoplastic Elastomer (TPE)	
Nominal Voltage	UL TC:	600V
	UL Flexible Motor Supply	1000V
	UL/CSA AWM:	1000V
Test Voltage	3000V:	16 AWG to 10 AWG
	3500V:	8 AWG to 4 AWG
	4000V:	2 AWG
Min Bend radius	For continuous flexing:	15 x OD
	For installation:	7.5 x OD

ÖLFLEX[®] VFD 1XL**UDB701700EN****Date:** March 15, 2020

Temperature Range	UL/CSA:	-25°C to +90°C
	For stationary use:	-40°C to +105°C
	For flexible use:	-25°C to +105°C
Cable Attributes	OR-03, FR-03, CF-01, MP-03 90°C Wet or Dry, Sunlight resistant, Direct Burial	
Approvals	UL Type TC (Tray Cable) - ER (Exposed Run) per UL 1277 UL Flexible Motor Supply Cable per UL 2277 UL AWM 22022 (Appliance Wiring Material) per UL 758 c(UL) CIC FT4 per CSA C22.2 No. 239 (14 AWG and smaller) cRU AWM II A/B FT4 per CSA C22.2 No. 210	
Additional	NEC Article 310, 336, Article 501 NFPA 79 RoHS II directive 2011/65/EU Meets XHHW-2 performance requirements	