


<b>7038889</b>	<b>DATA SHEET</b>	
<b>valid from: 2023-01-11</b>	<b>UNITRONIC® SENSOR FD Lif9Y11Y</b>	

## Application

UNITRONIC® SENSOR FD Lif9Y11Y are sensor/actuator cables, designed for applications in power chains.

## Design

Design	based on UL AWM Style 10493 (Insulation) and 20549 (Jacket), UL 758, CSA C22.2 No. 210 (80°C, 300 V)
Certification	UL AWM Style 20549 (File No. E63634), UL 758 RoHS AWM I/II A/B (File No. E63634)
Conductor	superfine wire strands of bare copper wires
Insulation	polypropylene
Core identification code	according to EN 60947-5-2 3-core: brown, blue, black 4-core: brown, white, blue, black 5-core: brown, white, blue, black, grey 8-core: white, brown, green, yellow, grey, pink, blue, red
Stranding	cores stranded to bundle, talced 5-core: central filler
Outer sheath	PUR Colour: black (similar RAL 9005)

## Diameter of the outer sheath

Article number	Dimension	Outer sheath $\phi$
7038883	3x0.25 mm <sup>2</sup>	ca. 4.4 mm
7038884	4x0.25 mm <sup>2</sup>	ca. 4.7 mm
7038867	5x0.25 mm <sup>2</sup>	ca. 4.7 mm
7038868	8x0.25 mm <sup>2</sup>	ca. 5.9 mm
7038864	3x0.34 mm <sup>2</sup>	ca. 4.6 mm
7038865	4x0.34 mm <sup>2</sup>	ca. 4.7 mm
7038866	5x0.34 mm <sup>2</sup>	ca. 5.1 mm
7038889	3x0.25 mm <sup>2</sup>	ca. 3.6 mm (optimized)
7038890	4x0.25 mm <sup>2</sup>	ca. 3.9 mm (optimized)
7038893	5x0.34 mm <sup>2</sup>	ca. 4.5 mm (optimized)

## Electrical properties at 20 °C

Conductor resistance	0.25 mm <sup>2</sup> : max. 79 $\Omega$ /km 0.34 mm <sup>2</sup> : max. 57 $\Omega$ /km
Specific volume resistivity	7x10 <sup>15</sup> $\Omega$ x cm
Maximum operating voltage	300 V (not for power applications) Must not be connected to the mains supply voltage.
Test voltage	C/C: 2000 V


## Mechanical and thermal properties

Minimum bending radius	Flexing: 10 x outer diameter Fixed installation: 5 x outer diameter
Temperature range	EN: Flexing: -25 °C up to +80 °C max. conductor temperature Fixed installation: -40 °C up to +80 °C max. conductor temperature UL AWM: up to +80 °C max. conductor temperature
Number of cycles	min. 4 mio. alternating bending cycles (max. 60 °C)
Travel distance	10 m length, min. 10 x cable $\phi$ , max. 3 m/s, max. 10 m/s <sup>2</sup>
Flammability	flame retardant acc. to UL 1581 FT-2
Halogen free	acc. to VDE 0472-815

## General requirements

These cables are conform to  
EU-Directive 2014/35/EU (Low Voltage Directive) and to  
EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain  
hazardous substances).

Creator: PESA / PDC	Document: DB7038889EN	Page 1 of 2
Released: ALTE / PDC	Version: 06	

7038889	<b>DATA SHEET</b>	
valid from: 2023-01-11	<b>UNITRONIC® SENSOR FD Lif9Y1 1Y</b>	

**Environmental information**

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: PESA / PDC Released: ALTE / PDC	Document: DB7038889EN Version: 06	Page 2 of 2
---	--------------------------------------	-------------